

MANUFACTURE, IMPORT, ASSEMBLY FULL ENGINEERING ACTIVITY



30 years of trust in the experience and professionalism of "LAKAL" Itd

HEATING INSTALLATIONS

PELLET BOILERS MCZ Compact-Italy



Fully automatic, it is a silent and compact solution for the heating of apartments, houses, cottages, or small public buildings.



It can be operated through auxiliary room thermostat or the water temperature, as the heat in the separate rooms is regulated by thermostatic valves. It can also be used for underfloor heating.



The weekly programmable control panel is user friendly and it can operate auxiliary DHW tank or puffer (optional).

MCZ Compact pellet boilers allow installation and easy operation in considerably small spaces like closets, under staircases, garages or other servicing rooms that provide access of combustion air. It has a high nominal performance up to 93%.

MCZ Compact are a newly developed compact pellet boilers with outputs of 14, 18, 24, 35 and 45kW.

With built-in: pellet hopper, circulation pump, expansion vessel, safety valve and weekly programmable control panel. It is certified in accordance with EN303-5, Class 5.


MCZ Compact have a built in anti-freeze protection and anti- lock function for the pump.





MCZ Compact

MCZ Compact Slim



- a. Control panel
- b. Cast iron brazier
- Large ash pan, allowing once a week cleaning
- d. Pellet hopper
- e. Hydraulic kit

With maximum space saving in the installation, a DHW tank with a volume of 110 l can be integrated to the existing heating system.

Operation of the tank can be automatically and easily achieved by the corresponding function in the control panel. The unit configuration enables the use of the **summer work mode** – only for hot water.

The boilers have **ECO STOP function**. After reaching the set temperature, the unit remains at a minimum output for at least 10min. before turning off. If during that time the water temperature falls, the boiler switches automatically to a normal mode, avoiding shut down and restart.

In this way **MCZ Compact** provides more dynamic operation, lower emissions and significant pellet economy.


The SLEEP function, the weekly programmable option and the long period of independent operation without servicing, make the boilers **MCZ Compact** practical, easy to use and a convenient solution for the heating of your home.

Technical data

| | | Compact SLIM 15 | Compact 14 | Compact 18 | Compact 24 | Compact 35 | Compact 45 |
|------------------------------------|------|--------------------|------------|------------|------------|------------|------------|
| Heatoutput | kW | 13,5-15* | 13-14,4* | 17-18,1* | 22-24,5* | 32-34,5* | 41-45* |
| Efficiency | % | 90 | 90,3 | 93,8 | 90,2 | 92,8 | 92,6 |
| Exhaust gas temperature | °C | 85 | 108 | 110 | 150 | 140 | 140 |
| Boiler water capacity | L | 20 | 20 | 25 | 25 | 30 | 50 |
| Maximum working pressure | bar | 3 | 3 | 3 | 3 | 3 | 3 |
| Dimensions (WxDxH) | cm | 109x28x121 | 55x60x114 | 60x66x122 | 60x66x124 | 74x70x134 | 77x87x133 |
| Weight | kg | 200 | 190 | 200 | 200 | 300 | 350 |
| Flue pipe | ØDmm | 80 | 100 | 100 | 100 | 100 | 100 |
| Pellet tank capacity | kg | 40 | 20 | 70 | 70 | 100 | 100 |
| Running time with one load-min/max | hour | 12-37 | 8-27 | 19-68 | 15-68 | 16-60 | 11-38 |
| Hourly consumption at min/max | kg/h | 1-3,1 | 0,85-3 | 1-3,6 | 1-4,8 | 1,3-6,7 | 2,6-9,5 |
| Inlet/outlet water | inch | 3/4"M | 3/4"M | 3/4"M | 3/4"M | 3/4"M | 3/4"M |
| Freshairinlet | ØDmm | 80 | 80 | 80 | 80 | 80 | 80 |

^{*} The maximum output depends of the quality of the pellets.

TECNICAL DATA



Stores:

PLOVDIV 4004; 136, NikolaVaptsarov Blvd., +359/32-673-020 VARNA 9000; 60A, Gen. Kolev Str., V. TARNOVO 5000; 1, Poltava Str.,

129

- +359/52-607-176
- +359/62-638-995

Head office:

BULGARIA, Plovdiv 4004; 136, Nikola Vaptsarov Blvd.

- +359/32-673-010 tel.
- +359/32-676-006 tel.
- +359/32-672-900 fax
- e-mail: office@lakal-bg.com, www.lakal-bg.com